

## ITURNADO 55 PRO

The all-rounder with a membrane tank

Our patented series of TURNADO 55 scrubber driers significantly reduces the required cleaning time. The scrubbing suction head of the TURNADO 55 machines, which can be rotated by up to 360°, ensures that even hard-to-reach areas can be cleaned by machine, making manual reworking unnecessary. The TURNADO 55 series is available in three different versions. As the PRO model, the TURNADO 55 is equipped with a stainless steel tank with membrane wall and thus holds 50 I of water, which is available for cleaning. The powerful TURNADO 55 machines are the all-rounders among our scrubber driers and can be used in almost all areas. Thanks to VERMOP ONe, the software solution from VERMOP, the TURNADO 55 can also be networked and is thus fully at home in the Internet of Things (IoT). The high-quality stainless steel chassis also comes with a 10-year warranty.



#### Areas of application

- Can be used for almost any application:
  Shops, salesrooms, storage and work halls, workshops, etc.
- Narrow storage areas and aisles due to TURNADO® Technology

#### Your advantages

- Digital networking
- \_360° rotatable scrubbing suction head (enormous manoeuvrability and flexibility thanks to patented TURNADO® technology)
- Longer usage times due to larger tank volume (for the PRO)
- \_Easy to use
- \_Extreme manoeuvrability due to compact design



# ITURNADO 55 PRO

The all-rounder with a membrane tank

TURNADO® technology, which even allows the machine to reach into corners and niches. Even when reversing, the head always turns independently in the working direction so that water application, cleaning and extraction can proceed in the correct sequence.

### Technical data

_Working width of brushes:	550 mm	_Theoretical cleaning rate:	2475 m²/h
_Working width vacuum barn:	680 mm	_Max. driving speed:	4.5 km/h
_Total length / height:	920 mm / 1150 mm	_Max. water supply:	3.5 I / min
_Clearance width:	670 mm	_Noise level:	75 dB / 69 dB BlueSave
_Tank volume (fresh/waste water):	see below	_Traction motor:	110 W
_Working time per battery charge:	approx. 2.5 h	_Brush motor:	2x 190 W
_Dead weight (including battery):	178 kg	_Vacuum motor:	500 W
_Gel battery, maintenance-free:	24 V, 105 Ah	_Brush diameter:	285 mm
_LiFePO4 battery:	24 V, 100 Ah	_Brush contact pressure:	2.2 N/cm²

The TURNADO 55 is available in the following versions (also with optional networking in each case):

\_ TURNADO 55: with 45 I fresh and waste water plastic tank

\_ TURNADO 55 SV: with 45 I fresh and waste water plastic tank as a special swimming pool version

\_ TURNADO 55 PRO: with 50 I fresh and waste water stainless steel tank with membrane wall